


# **VBA400-150**

10kHz- 400MHz 150W Amplifier

- Rugged push-pull MOSFET technology
- Class A for maximum mismatch drive
- General linear power requirements




Like all our products of the VBA400 series, it is based on rugged push-pull MOSFET technology, for extra even order harmonic suppression.



The amplifier operates in class A, the benefits for EMC applications being very low distortion and tolerance of 100% mismatch. Fold-back protection is neither fitted nor needed! This makes it supremely suited for very demanding transducer requirements.

## **Performance Chart**



Choose **Vectawave** for high efficiency and performance in your regular power amplifier requirements.

See overleaf for technical specification

#### Electrical

Frequency Range (Instantaneous) 10kHz-400MHz **Rated Output Power** 150W Min Output Power at 1dB Gain Compression 100W Min (>150W typical below 100MHz) Gain Third Order Intercept Point (see note 1) 61dBm ±2.5dB Gain variation with Frequency Better than -20dBc **Harmonics at 75W Output Power Output Impedance** 50 Ohms Stability Unconditional **Output VSWR Tolerance (see note 2)** Infinity:1 **Input VSWR** 2:1 (Max) 100 - 240V ac (+/- 10%) **Supply Voltage Supply Frequency Range** 45-63Hz <1kVA (Max) **Supply Power Mains Connector** IEC 320

#### Mechanical

RF Connector Style

Safety Interlock

USB/GPIB Interface

Dimensions

Mass

Operating Temperature Range

Case Style Options

Type N Female

Dual input, S/C and/or O/C to Mute

Optional

19 inch, 4U Case, 500mm Deep

18kg

0-40°C

Rack mount with Front or Rear panel connectors

Bench mount with Front panel connectors

### **Regulatory Compliance**

Conducted and Radiated EmissionsEN61326 Class AConducted and Radiated ImmunityEN61326:1997 Table 1SafetyEN61010-1

## Notes

- 1 The third order intercept point is a nominal value, as its calculation depends upon the power level at which distortion measurements are made.
- 2 Output VSWR tolerance is specified for excitation within the permitted levels and frequency range





**Designers and Manufacturers of Solid State RF and Microwave Amplifiers** 

## Represented Worldwide

Vectawave Technology Ltd.
Unit D, The Apex,
St Cross Business Park, Monks Brook,
Newport, Isle of Wight, PO30 5XW

**Tel:** +44 (0) 1983 821 818 **Fax:** +44 (0) 1983 532 737 **E-mail:** sales@vectawave.co.uk